MODEL:

PDUMV15NET

Switched Rackmount PDU















Low Voltage Input/Output

16 Outlets

15A Max Capacity


Load Meter

Network Interface

0U Rackmount


Toolless Mounting Buttons

- A Digital Load Meter
- **B** 5-15/20R Outlets with On/Off LEDs
- C Durable Metal Case
- Removable Cord
 Retention Brackets
- E Removable Mounting Brackets
- F Toolless Mounting Buttons
- **G** 10 ft. Input Power Cord
- H 5-15P Input Plug
- Network Interface
- J RJ45 Ethernet Jack
- K Manual Configuration Port
- L Environmental Monitoring Port
- M Network Interface Reset Button



AC Input Connection: Insert 5-15P plug into compatible 5-15R or 5-15/20R utility, generator or UPS outlet.

Also Includes: Cable Ties, Owner's Manual





temperature/humidity monitoring and dry contact interface.

- Remote monitoring and control via SNMP, Web or Telnet
- · Displays total load in real time
- Perfect for rackmount server, network and telecom applications

SEE NEXT PAGE FOR DETAILED UNIT MEASUREMENTS



1111 W. 35th Street Chicago, IL 60609 USA 773.869.1234 www.tripplite.com

Specifications

	(COMPLIANT)
Model	PDUMV15NET
Voltage	100-125V
Frequency	50/60 Hz
Maximum Capacity	15A
Agency-Derated Capacity	12A
Input Connector	5-15P
Cord Length	10 ft.
Outlets	16 (5-15/20R)
Primary Mounting Option	0U (Vertical) Rackmount
Unit Weight & Dimensions	7 lb / 4.25 x 49 x 2.25 in.
	See next page for detailed unit measurements.
Certifications	Tested to UL 60950-1 (US & Canada), NOM (Mexico),
	FCC Class A
Tripp Lite has a policy of continuous im	provement. Specifications are subject to change without notice.

